

DAMN GOOD GREY PLASTISOL INK

SDS Number: 3 Revision Date: 5/2/2018

Page 1 of 4

4

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Performance Screen Supply, LLC 600 Park Ave Manalapan, NJ 07726

Emergency: Chemtel 1-800-255-3924 Int'l 1-813-248-0585

Contact: Robert Drake Phone: +1-732-866-6081

Email: bob@performancescreen.com

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 2

Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING GHS Hazard Pictograms:



GHS Hazard Statements:

H315 - Causes skin irritation

H335 - May cause respiratory irritation

GHS Precautionary Statements:

No GHS precautionary statements indicated

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Inhalation;

Target Organs: Lungs;

Inhalation: Can cause irritation and inflammation of the respirtory tract.

Skin Contact: May cause irritation.

Eye Contact: May cause irritation.



DAMN GOOD GREY PLASTISOL INK

SDS Number: 3 Revision Date: 5/2/2018

Page 2 of 4

HMIS III: Health = 1(Chronic), Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves





3

COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

OSHA Regulatory Status:

This MSDS Contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

Cas#	%	Chemical Name
9002-86-2		Ethene, chloro-, homopolymer
9003-22-9		Acetic acid ethenyl ester, polymer with chloroethene
27138-31-4		Propanol, oxybis-, dibenzoate
474919-59-0		CYCLOHEXANEDICARBOXYLIC ACID DINONYL EST
13463-67-7		Titanium oxide (TiO2)
1317-65-3		Calcium carbonate
6846-50-0		Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester
57455-37-5		C.I. Pigment Blue 29
80-51-3		Benzenesulfonic acid, 4,4'-oxybis-, dihydrazide
1333-86-4		Carbon black

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact: Wash with soap and water.

Eye Contact: Flush with large amounts of water.

Ingestion: Get prompt, qualified medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: No Data Available

Autoignition Temp: N/A

6 ACCIDENTAL RELEASE MEASURES

Do not discharge into drains.

Pick up excess with inert absorbant material and place into separate waste container.



DAMN GOOD GREY PLASTISOL INK

SDS Number: 3 Revision Date: 5/2/2018

Page 3 of 4

7

HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing. Keep material out of reach of children.

Storage Requirements: Keep away from heat, sparks, and flames.

Я

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Use mechanical (general) ventilation for storage areas.

Personal Protective

HMIS PP, C | Safety Glasses, Gloves, Apron

Equipment:

HMIS PP, B | Safety Glasses, Gloves

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White

Physical State: Liquid Particle Size: N/A

Viscosity: Between 100,000 - 150,000 cps

Odor: Faint Odor

Molecular Formula: N/A Softening Point: 200C

10

STABILITY AND REACTIVITY

Chemical Stability: Product is stable under normal conditions.

Conditions to Avoid: Exposure to excessive heat

Hazardous Decomposition: Not known.

Hazardous Polymerization: Will not occur.

11

TOXICOLOGICAL INFORMATION

The mixture as a whole has not been evaluated for health effects

12

ECOLOGICAL INFORMATION

Persistance and degradability: Not readily biodegradable

Environmental toxicity: Environmental toxicity has not been determined for this mixture as a whole

Bioaccumulation potential: No data available

Additional advice: No data available

13

DISPOSAL CONSIDERATIONS

Dispose of properly according to State and Federal Regulations



DAMN GOOD GREY PLASTISOL INK

SDS Number: 3 Revision Date: 5/2/2018

Page 4 of 4

14

TRANSPORT INFORMATION

DOT Class: Not regulated #

Refer to specific regulations

15

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Ethene, chloro-, homopolymer (9002-86-2) [n/a%] TSCA

Acetic acid ethenyl ester, polymer with chloroethene (9003-22-9) [n/a%] TSCA

Propanol, oxybis-, dibenzoate (27138-31-4) [n/a%] TSCA

CYCLOHEXANEDICARBOXYLIC ACID DINONYL EST (474919-59-0) [n/a%]

Titanium oxide (TiO2) (13463-67-7) [n/a%] MASS, OSHAWAC, PA, TSCA, TXAIR

Calcium carbonate (1317-65-3) [n/a%] MASS, OSHAWAC, PA, TSCA, TXAIR

Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester (6846-50-0) [n/a%] TSCA

C.I. Pigment Blue 29 (57455-37-5) [n/a%] TSCA

Benzenesulfonic acid, 4,4'-oxybis-, dihydrazide (80-51-3) [n/a%] TSCA

Carbon black (1333-86-4) [n/a%] MASS, OSHAWAC, PA, TSCA, TXAIR

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act
MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

16

OTHER INFORMATION

The information provided in this SAFETY DATA SHEET is correct to the best of our knowledge,information and belief at the date of its publication. The information given is designed only as a guidance for safety,handling,use,processing,storage,transportation,disposal and release and is not to be considered a warranty or quality specification. The information relates only to specific materials desighned and may not be valid for such materials used in combination with any other materials or in any process,unless specified in the text