

GHS Safety Data Sheet

SUPER HI-TEST WHITE PLASTISOL INK

SDS Number: 3

Revision Date: 5/2/2018

Page 1 of 4

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

1

2

Performance Screen Supply, LLC 600 Park Ave Suite 100 Manalapan, NJ 07726

Emergency:	Chemtel 1-800-255-3924 Int'l 1-813-248-0585
Contact:	Robert Drake
Phone:	+1-732-866-6081
Email:	bob@performancescreen.com

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 2

Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:



GHS Hazard Statements:

H315 - Causes skin irritation H335 - May cause respiratory irritation

GHS Precautionary Statements:

No GHS precautionary statements indicated

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry:	Eyes; Inhalation;
Target Organs:	Lungs;
Inhalation:	Can cause irritation and inflammation of the respirtory tract.
Skin Contact:	May cause irritation.
Eye Contact:	May cause irritation.



GHS Safety Data Sheet

SUPER HI-TEST WHITE PLASTISOL INK

SDS Number: 3

Revision Date: 5/2/2018

Page 2 of 4

HMIS III:Health = 1(Chronic), Fire = 0, Physical Hazard = 0HMIS PPE:B - Safety Glasses, Gloves

HMIS	PPE
HEALTH 🔽 1	
FLAMMABILITY 0	
PHYSICAL HAZARD 0	
PERSONAL PROTECTION B	

COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

3

OSHA Regulatory Status:

This MSDS Contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

Cas#	%	Chemical Name
$\begin{array}{c}$		Ethene, chloro-, homopolymer Acetic acid ethenyl ester, polymer with chloroethene Propanol, oxybis-, dibenzoate CYCLOHEXANEDICARBOXYLIC ACID DINONYL EST Titanium oxide (TiO2) Calcium carbonate Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester C.I. Pigment Blue 29
80-51-3		Benzenesulfonic acid, 4,4'-oxybis-, dihydrazide

FIRST AID MEASURES

Inhalation:If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.Skin Contact:Wash with soap and water.Eye Contact:Flush with large amounts of water.Ingestion:Get prompt, qualified medical attention.

FIRE FIGHTING MEASURES

Flash Point:No Data AvailableAutoignition Temp:N/A

6

5

4

ACCIDENTAL RELEASE MEASURES

Do not discharge into drains.

Pick up excess with inert absorbant material and place into separate waste container.



GHS Safety Data Sheet

SUPER HI-TEST WHITE PLASTISOL INK

SDS Number: 3

Revision Date: 5/2/2018

Page 3 of 4

7	HANDLING AND STORAGE
Handling Precautions: Storage Requirements:	Avoid contact with eyes, skin, or clothing. Keep material out of reach of children. Keep away from heat, sparks, and flames.
8	EXPOSURE CONTROLS/PERSONAL PROTECTION
Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).
Personal Protective Equipment:	Use mechanical (general) ventilation for storage areas. HMIS PP, C Safety Glasses, Gloves, Apron HMIS PP, B Safety Glasses, Gloves

9	PHYSICAL AND CHEMICAL PROPERTIES			
Appearance: Physical State: Particle Size: Viscosity:	White Liquid N/A Between 100,000 - 150,000 cps	Odor: Molecular Formula: Softening Point:	Faint Odor N/A 200C	
10	STABILITY AND REACTIVITY			

Chemical Stability:	Product is stable under normal conditions
Conditions to Avoid:	Exposure to excessive heat
Hazardous Decomposition:	Not known.
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

The mixture as a whole has not been evaluated for health effects

12 ECOLOGICAL INFORMATION

Persistance and degradability: Not readily biodegradable

Enviromental toxicity: Enviromental toxicity has not been determined for this mixture as a whole

Bioaccumulation potential: No data available

Additional advice: No data available

13

DISPOSAL CONSIDERATIONS

Dispose of properly according to State and Federal Regulations



SUPER HI-TEST WHITE PLASTISOL INK

SDS Number: 3

Revision Date: 5/2/2018

Page 4 of 4

14

TRANSPORT INFORMATION

DOT Class: Not regulated #

Refer to specific regulations

15

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Ethene, chloro-, homopolymer (9002-86-2) [n/a%] TSCA

Acetic acid ethenyl ester, polymer with chloroethene (9003-22-9) [n/a%] TSCA

Propanol, oxybis-, dibenzoate (27138-31-4) [n/a%] TSCA

CYCLOHEXANEDICARBOXYLIC ACID DINONYL EST (474919-59-0) [n/a%]

Titanium oxide (TiO2) (13463-67-7) [n/a%] MASS, OSHAWAC, PA, TSCA, TXAIR

Calcium carbonate (1317-65-3) [n/a%] MASS, OSHAWAC, PA, TSCA, TXAIR

Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester (6846-50-0) [n/a%] TSCA

C.I. Pigment Blue 29 (57455-37-5) [n/a%] TSCA

Benzenesulfonic acid, 4,4'-oxybis-, dihydrazide (80-51-3) [n/a%] TSCA

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

The information provided in this SAFETY DATA SHEET is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safety, handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to specific materials designed and may not be valid for such materials used in combination with any other materials or in any process, unless specified in the text

